



NOTES:

- 1) FIBER-PureWave® XL55 OR SL55
- 2) RANDOMIZED
- 3) MIN. BEND RADIUS-2"

PART NUMBER	LENGTH	REV
FTIIG16860-20	20"	A
FTIIG16860-40	40"	A
FTIIG16860-60	60"	A
FTIIG16860-72	72"	A
FTIIG16860-80	80"	A
FTIIG16860-120	120"	A

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FIBEROPTICS TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FIBEROPTICS TECHNOLOGY IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±2° TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	DRAWN MH	04/17/2020
INTERPRET GEOMETRIC TOLERANCING PER:	CHECKED SG	07/10/2020
MATERIAL -	ENG APPR. SG	08/07/2020
FINISH -	MFG APPR.	
DO NOT SCALE DRAWING	Q.A.	
	COMMENTS:	

**FIBEROPTICS TECHNOLOGY**

TITLE:  $\phi$  .250  
**MACHINE VISION  
LIGHT GUIDE**

SIZE <b>A</b>	DWG. NO. <b>SEE CHART</b>	REV SEE CHART
------------------	------------------------------	------------------

SCALE: 1:1 SHEET 1 OF 1